

RTR05 Series

	Specification & Capacities	
Model Number	RTR0542	RTR0550
Recommended Tractor PTO HP	Up to 25 Horsepower (Subcompact Tractors)	
Weight	268#	298#
Tilling Width	42"	50"
Overall Width	46 1/2"	54 1/2"
Hitch Type	Category I Fits Land Pride's Category I Quick Hitch	
Offset Capabilities	No	
Number of flanges	5	6
Number of tines per flange	4	
Tine Construction	Alloy steel heat treated "C" shaped blades	
Skid Shoes	Adjustable	
Storage Stands	Adjustable	
Rear Deflector	Adjustable	
Driveline	Category II Off-Center Shear-bolt - standard Slip-Clutch - optional	
Gearbox	25 HP input at 540rpm 1.46:1 ratio Cast iron housing, straight bevel gears	
Gearbox Lubrication & Oil Capacity	1 Pint of SAE 80-90W EP oil	
Drive Chain	#80 Roller chain - Fully enclosed in oil bath with drain & fill plugs	
Drive Chain Lubrication	Shell Gadus S2 V2200 00 flowable grease or equivalent Land Pride Part #821-045C (32 oz. bottle)	
Sprockets	Case hardened teeth, splined bores	
Rotor Swing Diameter	13"	
Rotor Shaft Speed	230 rpm at 540 rpm PTO	

