



For Earth, For Life
Kubota

L

KUBOTA DIESEL TRACTOR L2501

With the power to tackle a wide range of jobs, Kubota's New L2501 combines robust performance and user-friendly features in one easy-to-operate compact tractor.



Powerful enough to tackle a wide range yet nimble enough to provide the precision

ENGINE



Powerful, clean running Kubota diesel engines

Kubota engines are well known for their reliability, power, and ability to generate outstanding horsepower. Today, Kubota engines are more fuel efficient and clean running than ever before. The 24.8 HP (18.5kW) engine in the L2501 meets the very latest EPA Tier 4 Final emission regulations. And, maintenance is easier with a gas-strut hood opener-assist.

COMFORT



Enhanced operator's deck

The L2501 features a spacious operator's platform for optimal comfort. The ergonomic design means that the operator experiences less fatigue. The semi-flat design of the deck makes mounting and dismounting the tractor easier.



HST Transmission with 4WD

The HST transmission offers simple forward and reverse change and 3-range shifting for optimal operating efficiency. Optional cruise control is also available.



of tasks, ion performance you need.



VERSATILE APPLICATION

Performance Matched Implements

- LA525 Front Loader
Maximum lift capacity (pivot pin) is 1131 lbs, with a maximum lift height of 94.3".
- BH77 Backhoe
- Rear Rotary Cutter max. cutting width 60"
- Rear Snow Blower
- Rotary Tiller, Rear Blade, and more

2-lever-quick Coupler

The quick coupler is simple to use. Quick, easy on/off buckets and other attachments require no tools, only mounting pins and hose couplers, allowing you to move onto the next task in a matter of minutes.



Specifications

Model			L2501
			HST
			4WD
Engine			
Type	Direct injection, Vertical, Water-Cooled 4 cycle diesel		
Engine gross power*	HP (kW)	24.8 (18.5)	
Engine net power**	HP (kW)	23.9 (17.8)	
PTO power	HP (kW)	19.0 (14.2)	
No. of cylinders	3		
Bore & stroke	in. (mm)	3.4 × 3.6 (87 × 92.4)	
Total displacement	cu. in. (cm ³)	100.47 (1647)	
Rated speed	rpm	2200	
Battery	12V, RC: 123 min, CCA: 490 A		
Alternator	12V, 40A		
Fuel tank capacity	US gal. (ℓ)	10.0 (38.0)	
PTO			
Rear PTO type	Live-continuous running		
PTO/Engine speed	540/2105		
Hydraulic			
Lift control type	Position control		
Pump capacity (main)	gpm (ℓ/min)	5.15 (19.5)	
(PS)	gpm (ℓ/min)	3.13 (11.8)	
3-point hitch	Category I		
Lift capacity at lift points	lbs. (kg)	1918 (870)	
24 in. behind lift points	lbs. (kg)	1389 (630)	
System pressure	PSI (MPa)	2205 (15.2)	
Travelling System			
Transmission	Hydrostatic transmission, 3 range speed		
Steering	Integral type power steering		
Brake	Wet disc type		
Clutch	Dry type single stage		
Tire size	AG Standard	Front/Rear	7.2 - 16/11.2 - 24
	Indust. Option	Front/Rear	27 × 8.50 - 15/15 - 19.5 R4
Traveling speed with standard AG tires	mph (km/h)		Forward 0 (0.0) - 11.5 (18.5) Reverse 0 (0.0) - 10.3 (16.6)
Dimensions			
Overall length (w/o 3P)	in. (mm)	106.3 (2700)	
Overall width (min. tread)	in. (mm)	55.1 (1400)	
Overall height (w/Foldable ROPS)	in. (mm)	91.7 (2330)	
Wheelbase	in. (mm)	63.3 (1610)	
Min. ground clearance	in. (mm)	13.4 (340)	
Tread	Front tire	43.1 (1095)	
	Rear tire	43.8 (1115) / 47.1 (1195) / 50.8 (1290)	
Min. turning radius (w/brake, 4WD disengaged)	feet (m)	8.2 (2.5)	
Weight (with ROPS)	lbs. (kg)	2623 (1190)	

* SAE J1995

** SAE J1349

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information. For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications.

©2014 Kubota Corporation

Kubota®

KUBOTA CANADA LTD.

Head Office:
5900 14th Avenue, Markham, Ontario L3S 4K4
TEL: (905) 294-7477

Visit our web site at: www.kubota.ca

