

### SC7072 Skid Cutter

#### Specifications & Capacities

Specifications & Capacities	
<b>Model Numbers</b>	<b>SC7072</b>
<b>Cutter weight with skid shoes</b>	2580lbs.
<b>Hitch</b>	Welded on
<b>Cutting width</b>	73-1/2"
<b>Overall width</b>	84-3/8"
<b>Overall length</b>	92-1/4"
<b>Cutting height</b>	1 1/2" to 18" infinitely variable.
<b>Cutting capacity</b>	7" Diameter
<b>Spindle hub oil capacity</b>	85 oz.
<b>Spindle hub oil</b>	EP 80-90 wt. gearlube
<b>High volume drive motor</b>	26-43 gpm flow
<b>Hydraulic pressure</b>	Up to 3500 psi.
<b>Deck thickness</b>	1/4"
<b>Side skirt construction</b>	1/4" Steel
<b>Deck wear protection</b>	Four, corner-mounted skid shoes
<b>Skid shoe construction</b>	3/8" plate
<b>Blade Carrier</b>	(2) Round 1/2" plate weldments
<b>Blade size</b>	3/4" double edge
<b>Blade rotation</b>	Clockwise
<b>Blade bolt</b>	3/4-10 Grade 8
<b>blade tip speed</b>	11,870 fpm at 43 gpm.
<b>Front deck protection</b>	Bi-fold door with single row chain guard
<b>Rear deck protection</b>	Single row chain guard
<b>Deck lift height protection</b>	Height adjustment safety chain
<b>Mulching teeth</b>	3/4" SQ carbide