



For Earth, For Life
Kubota

B

KUBOTA DIESEL TRACTOR B3350SU Special Utility Tractor

The new B3350SU tractor with a powerful diesel engine brings comfort to a variety of task handling jobs.

Our most powerful B-Series tractor ever combines user-friendly operation and versatility with a wide variety of implements.

Diesel Engine

The B3350SU's liquid-cooled E-TVCS (Emission-Three Vortex Combustion System) diesel engine delivers 30.8HP (27 PTO HP) with high torque for the tractor strength you need, combined with reduced emissions. The B3350SU's Diesel Particulate Filter (DPF) Muffler is compliant with the latest Tier IV emission regulations.

3-Range Transmission

Our proven hydrostatic transmission provides the B3350SU with powerful and smooth shifting performance for heavy-duty loader applications. Range gears can be set between Low, Mid, and High to match a variety of operations.



3-Point Hitch

The capable PTO horsepower and a Powerful Category I 3-point hitch ensures easy attaching and detaching of implements, such as a rotary cutter, box blade and finishing mower. The intuitive clutch-less PTO engagement simplifies operation.



Hydrostatic Power Steering

The power steering is hydraulically controlled for comfortable and nimble handling to reduce fatigue during prolonged operation.

Additional Features

- One Piece Metal Hood
- Foldable ROPS
- Optional BH77 Backhoe with Reversible Seat
- Optional 2-Lever Quick Coupler for Front Loader Attachment
- Optional Large Industrial Tires
Front: 25 x 8.5 - 14 Rear: 15 - 19.5)



*Shown with optional 3rd function valve and hydraulic spill guard

Brochure Disclaimer:
This brochure contains information that **may not** be accurate for the Canadian Market.

Specifications

Model	B3350SUHSD	
Engine		
Type	E-TVCS, liquid cooled, 4-cylinder diesel	
Make, Model	V1505-T-E4-D26-R	
PTO horsepower	HP (kW)	27.0 (20.1)
Engine gross horsepower*	HP (kW)	30.8 (23.0)
Rated RPM	rpm	2500
Bore and stroke	in. (mm)	3.1 × 3.1 (78 × 78.4)
Displacement	cu. in. (cc)	91.5 (1498)
Air cleaner	4.5 inch Dual paper element	
Lubrication	Forced lubrication	
Cooling system	Pressurized radiator	
Radiator fan	Radial air flow	
Capacities		
Fuel tank	gal (ℓ)	7.3 (27.5)
Cooling system	qts. (ℓ)	4.5 (4.3)
Engine oil	qts. (ℓ)	5.1 (4.8)
Transmission case	gal (ℓ)	4.0 (15)
Drive train		
Clutch	N / A	
Transmission	HST (3 ranges)	
Differential lock	Standard	
Final drive	Spur gear	
Brake	Multi-plate wet disc	
PTO		
Type	Independent	
Rear	rpm	540
Hydraulics		
Type	Open center	
Pump	Dual pump	
Total pump output	gpm (ℓ/min.)	8.7 (33.1)
Hydraulic outlet	Rear outlet	
3-point hitch	Category I	
Hydraulic control system	Quarter inching valve	
Lift capacity	at lift point lbs. (kg)	2139 (970)
	24" behind LP lbs. (kg)	1676 (760)
Steering	Hydraulic power steering	
Standard tire size		
Front (Farm)	7-12	
Rear (Farm)	12.4-16	
Traveling speeds (at rated engine rpm)		
Forward	mph (km/h)	0-14.3 (0-23.0)
Reverse	mph (km/h)	0-11.4 (0-18.4)
Dimensions		
Overall length (w/o 3P)	in. (mm)	101.2 (2570)
Overall width (min. tread)	in. (mm)	53.7 (1365)
Overall height	in. (mm)	78.5 (1995)
Wheelbase	in. (mm)	65.6 (1666)
Ground clearance	in. (mm)	14.6 (370)
Turning radius with brake	feet (m)	6.9 (2.1)
Weight	lbs. (kg)	1874 (850)
Other Features	Coil spring suspension seat, Drawbar, Tool box, 12V Power socket	

*SAE J1995

Kubota Canada Ltd. reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for Canada only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.



KUBOTA CANADA LTD.

Head Office:
5900 14th Avenue, Markham, Ontario L3S 4K4
TEL: (905) 294-7477

Visit our web site at: www.kubota.ca

©2019 Kubota Corporation

